

# TECHNICAL DATA SHEET

## S0 FAST CUT MEDIUM GLOSS



### Polishing Liquid Compound



#### PRODUCT DESCRIPTION

Polishing compound S0 FAST CUT & MEDIUM GLOSS is the less aggressive paste recommended for manufactures. Doesn't contain silicon and waxes.

#### PRODUCT INFORMATION

SURFACE TYPE	gelcoat, tool gelcoat, medium-hard industrial paint		
EFFECT	removal of scratches from medium-hard surface, removal of yellowing on bright color surface, dull on dark surface, chalky		
CATEGORY	production		
PRODUCT TYPE	MULTISTAGE <b>1 stage</b> : polishing compound S0 – removal scratches, medium gloss level <b>2 stage</b> (optional) : polishing compound S1 - removal polishing defects arise on first stage, increase gloss level		
COLOR	white		
DENSITY	1,49 kg/l		
CONSISTENCY	paste		
METHODE OF POLISHING	machine		
MACHINE TYPE	rotary machine		
APPLICATOR	sheep wool, lamb wool, hard sponges		
CUT LEVEL		8/10	
GLOSS LEVEL		6/10	

#### INSTRUCTION FOR USE

SURFACE PREPARATION	<p>Wash surface using Sea-Line S3 FINISH CLEANER SHINE CONTROL.</p> <p>If removing defects from surface is necessary, grind it and finish sanding on minimal gradation:</p> <ul style="list-style-type: none"> <li>• Gelcoat, paints (finished products, bright colors): minimum P800 or higher</li> <li>• Gelcoat, paints (finished products, dark colors): minimum P1200 or higher</li> <li>• tool gelcoat: minimum P1200 or higher</li> </ul> <p>Remove dust after sanding.</p> <p>Once again wash surface using S3</p>
FIRST STAGE OF POLISHING	<p>Apply polishing compound S07 onto surface or applicator.</p> <p>Start polishing from the lowest rotation speed (800-1000 RPM) until compound starts to change color</p> <p>Slowly increase rotation speed to max. 1800 RPM, if it's necessary, deeper scratches remove by gently pushing machine to surface</p> <p>Polish until all defects are removed and full gloss obtained.</p> <p>Remove dust and all residues left from polishing process using S3 FINISH CLEANER</p> <p>If necessary repeat polishing process.</p>
SECOND STAGE (OPTIONAL)	<p>To remove microdefects arising from use S0 and increase gloss:</p> <ul style="list-style-type: none"> <li>• Sea-Line® S1 SOFT CUT &amp; GLOSS</li> </ul>

# TECHNICAL DATA SHEET

## S0 FAST CUT MEDIUM GLOSS

### Polishing Liquid Compound



#### FURTHER WORK

To remove holograms and increase gloss:

- Sea-Line® S2 HOLOGRAM REMOVER

For protection surface use:

- Sea-Line® S4 WAX or Sea-Line® S5 QUICK WAX

#### IMPORTANT NOTES

The elements that have influence on end effect are:

- Surface preparation by choosing correct gradation of sand papers
- Applicator type

Details on [www.sea-line.eu](http://www.sea-line.eu)

#### STORAGE AND SAFETY INFORMATION

##### SHELF LIFE

24 months from production

##### STORAGE

Product components should be stored in tightly sealed containers, in a temperature of 10-25°C, away from sources of fire, heat and sunlight. Close container tightly immediately after each use. Store in a dry place and keep sealed cans until use. Keep away from children. Protect from frost.

##### HSE CONDITIONS

Please follow safety instructions from the Safety Data Sheet and follow workplace safety laws. The general rule is to avoid contact of the product with the skin and eyes. Notice ! Always follow all precautionary, health and safety notice on the Safety Data Sheet and container labels.

##### DISCLAIMER

All data in this document have been prepared for informational purpose only. We can not take responsibility for the results of user actions over which we have no control. The user is responsible for making the control sample and determining the suitability of the product for specific, individual applications. Company Troton Sp. z o.o. does not take responsibility for any damage, or loss of profits associated with the improper use of the products. All information is based on scrupulous laboratory research and many years of experience. Our position of market leadership does not free us from constant quality control of our products. However, we do not accept responsibility for the effects of improper use or storage of our products, or the effects of using our products in any way contrary to the standard of good workmanship.

##### QUALITY QUARANTEE

Production, quality control and the realization of deliveries fulfill the demands of ISO 9001 and 14001 standards.