







































# COMPATIBILITY CHART ANTIFOULING Sea-Line®

## NEW ANTIFOULING PAINT SEA-LINE®

- SELF-POLISHING
- ALU PLUS Self-polishing
- POLISHING - Silver Cruise
- SEGUARD Fouling Stop

- HARD ANTIFOULING
- HARD - Silver Speed






- THIN FILM - Silver Racing

CURRENT COAT ANTIFOULING	SEA-LINE®	<ul style="list-style-type: none"> <li>SELF-POLISHING</li> <li>ALU PLUS SELF-POLISHING</li> <li>POLISHING – Silver Cruise</li> <li>SEAGUARD</li> </ul>		 	 
		<ul style="list-style-type: none"> <li>HARD antifouling</li> <li>HARD - Silver Speed</li> </ul>			
		<ul style="list-style-type: none"> <li>THIN FILM - Silver Racing</li> </ul>	 	 	
	OLD ANTIFOULING	<ul style="list-style-type: none"> <li>Unknown product in good condition</li> </ul>	 	 	 
		<ul style="list-style-type: none"> <li>Self- polishing antifouling in good condition</li> </ul>		 	 
		<ul style="list-style-type: none"> <li>Hard antifouling in good condition</li> </ul>			
		<ul style="list-style-type: none"> <li>Antifouling type THIN FILM in good condition</li> </ul>	 	 	
		<ul style="list-style-type: none"> <li>Previous antifouling in poor condition</li> </ul>	 	 	 

### Do not risk !

If existing antifouling coat is in bad condition, remove it !

### Basic recommendation for surface preparation and paint application Sea-Line® :

<ul style="list-style-type: none"> <li>➤ Use biocides safely. Always read the label and product information before use</li> <li>➤ When using the product in a small, enclosed space you must provide forced ventilation</li> <li>➤ Avoid contact of liquid with eyes and skin</li> <li>➤ Please follow safety instructions from the technical data sheet for hazardous chemical and follow workplace safety laws</li> </ul>		<ul style="list-style-type: none"> <li>• Clean old surface with water under pressure (remove splinters and repair damage on the surface)</li> <li>• Abrade P100-P240 all surface</li> <li>• places after repair or grinded surfaces from antifouling paint protect using 1K UNIVERSAL PRIMER Sea-Line®</li> <li>• Apply 1-3 layers of Sea-Line antifouling</li> </ul>
	 	<ul style="list-style-type: none"> <li>• Clean old surface with water under pressure (remove splinters and repair damage on the surface)</li> <li>• Abrade P100-P240 all surface</li> <li>• Apply a barrier coat of 1K UNIVERSAL PRIMER Sea-Line®</li> <li>• Apply 1-3 layers of Sea-Line antifouling</li> </ul>
	 	<ul style="list-style-type: none"> <li>• Remove all layers of old antyfoulingP100-P240 all surface</li> <li>• Apply minimum 1 layer primer: <ul style="list-style-type: none"> <li>▪ 2K Epoxy Lightprimer 5:1 Sea-Line® - laminates (GRP)</li> <li>▪ 2K Epoxy Anticorrosive 4:1 Sea-Line® - steel, aluminium</li> <li>▪ 2K Epoxy Woodprimer 10:4 Sea-Line® - wood</li> <li>▪ 1K UNIVERSAL PRIMER Sea-Line® - laminates, steel, wood,</li> </ul> </li> <li>• Apply by 1-3 of layers Sea-Line antifouling</li> </ul>