

Page 1/12

Safety data sheet (English translation without any country-specific legislation) according to 1907/2006/EC, Article 31

Printing date 25.11.2022

Rev. n. 3

Revision: 25.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: <u>BPO paste</u> PERVELOX EVO 50 - E02

1.2 Relevant identified uses of the substance or mixture and uses advised against

Formulation and packing into small containers. Industrial use as polymerisation initiator for production of polymers, and as cross-linking agent for the manufacture of resins. Professional use as hardener for coating resins. [SU 9, SU 10, SU12, SU 22] [PROC 3, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 11, PROC

[SU 9, SU 10, SU 12, SU 22] [PROC 3, PROC 5, 13, PROC 14, PROC 19, PROC 21]

- Application of the substance / the mixture Dibenzoyl peroxide, pasta Hardening agent / Curing agent Polymerisation catalyst
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: RAICHEM S.p.A.
 Via Don Grazioli, 53 - Località Gavassa
 42122 Reggio Emilia (Italy)
 Tel. +39 0522 511182 - Fax +39 0522 920616

· Further information obtainable from: RAICHEM S.p.A. - E-mail: laboratorio@raichem.it

· 1.4 Emergency telephone number:

- ITALY POISÓN CENTRES (24h / 365d):
- Milano Ospedale Niguarda Ca' Granda Tel. +39 02 66101029
- Pavia Centro Nazionale di Informazione Tossicologica IRCCS Fondazione S. Maugeri Tel. +39 0382 24444
- Firenze Azienda Ospedaliero-Universitaria "Careggi" U.O. Tossicologia Medica Tel. +39 055 7947819
- Bergamo Azienda Öspedaliera Papa Giovanni XXIII Tel. +39 800 883300
- Roma CAV Policlinico "Umberto I" Tel. +39 06 49978000
- Roma CAV Policlinico "A. Gemelli" Tel. +39 06 3054343
- Roma CAV "Ospedale Pediatrico Bambino Gesù" Tel. +39 06 68593726
- Foggia Azienda Ospedaliero-Universitaria Foggia Tel. +39 0881 732326
- Napoli Azienda Ospedaliera "A. Cardarelli" Tel. +39 081 7472870
- Verona CAV Azienda ospedaliera universitaria integrata (AOUI) Borgo Trento Tel. 8+39 00 011 858

RAICHEM S.p.A. - Technical support: Tel. +39 0522 511182 (Monday-Friday: 8.00-12.00 AM, 2.00-6.00 PM)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Org. Perox. E	H242 Heating may cause a fire.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
Aquatic Acute 1	H400 Very toxic to aquatic life.
Aquatic Chronic 1	H410 Very toxic to aquatic life with long lasting effects.

· 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Warning

- · Hazard-determining components of labelling:
- dibenzoyl peroxide
- Hazard statements
 H242 Heating may cause a fire.



Printing date 25.11.2022

P101

P102

Revision: 25.11.2022

Page 2/12

Trade name: BPO paste PERVELOX EVO 50 - E02

> H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

Precautionary statements

(Contd. of page 1) H410 Very toxic to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Wear protective gloves / eye protection / face protection.

P280 P302+P352 IF ON SKIN: Wash with plenty of soap and water.

Keep out of reach of children.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Rev. n. 3

Store in a well-ventilated place. Keep cool. P403+P235

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

· Components:		
CAS: 94-36-0	dibenzoyl peroxide	45-52%
EINECS: 202-327-6	🔶 🚸 Org. Perox. B, H241; 🚸 Aquatic Acute 1, H400 (M=10); Aquatic	
Index number: 617-008-00-0	Chronic 1, H410 (M=10); () Eye Irrit. 2, H319; Skin Sens. 1, H317	
Reg.nr.: 01-2119511472-50-XXXX		
CAS: 131-11-3	dimethyl phthalate	25-35%
EINECS: 205-011-6	substance with a Community workplace exposure limit	
Reg.nr.: 01-2119437229-36-XXXX		
CAS: 107-21-1	ethanediol	0.1-9.9%
EINECS: 203-473-3	🚸 STOT RE 2, H373; 🚸 Acute Tox. 4, H302	
Index number: 603-027-00-1 Reg.nr.: 01-2119456816-28-XXXX		
5		
· Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

4.1 Description of first aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

• Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released: Carbonic anhydride (CO2) Carbon monoxide (CO)



Printing date 25.11.2022

Rev. n. 3

Revision: 25.11.2022

Trade name: BPO paste PERVELOX EVO 50 - E02

(Contd. of page 2)

Benzoic acid Benzene Biphenyl Phenyl benzoate Under certain fire conditions, traces of other toxic gases cannot be excluded.

• 5.3 Advice for firefighters

Protective equipment: Do not inhale explosion gases or combustion gases. Mouth respiratory protective device. Wear suitable fire protection equipment. Additional information

Cool endangered receptacles with water spray. Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

• **6.1 Personal precautions, protective equipment and emergency procedures** Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Use respiratory protective device against the effects of fumes/dust/aerosol.

- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
 Do not allow to dry out Ensure adequate ventilation.

• 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 7 for information on sale nariding. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Use only in well ventilated areas. Ensure good ventilation/exhaustion at the workplace. Keep away from heat and direct sunlight. Protect against electrostatic charges.

- Information about fire and explosion protection: Substance/product is oxidising when dry.
 Keep ignition sources away - Do not smoke.
- 7.2 Conditions for safe storage, including any incompatibilities
 - Storage:
 - **Requirements to be met by storerooms and receptacles:** Store in a cool location. Store only in the original receptacle.
 - · Information about storage in one common storage facility:
 - Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.
 - Further information about storage conditions:
 - Store receptacle in a well ventilated area. Prevent from drying out.
 - Keep container tightly sealed.
 - Protect from heat and direct sunlight.

The product, stored in the original containers, away from sunlight, maintains its properties for 12 months from the production date.

· Recommended storage temperature: +5°C / +25°C

(Contd. on page 4)



Printing date 25.11.2022

Rev. n. 3

(Contd. of page 3)

Trade name: BPO paste PERVELOX EVO 50 - E02

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters				
· Ingredients with limit values that require monitoring at the workplace:				
94-36-0 dibenzoyl peroxide				
TWA (Italy)				
PEL (USA)	Long-term value: 5 mg/m³			
REL (USA)	Long-term value: 5 mg/m³			
TLV (USA)				
131-11-3 din	nethyl phthalate			
TWA (Italy)	Long-term value: 5 mg/m ³			
PEL (USA)	Long-term value: 5 mg/m ³			
REL (USA)	Long-term value: 5 mg/m ³			
TLV (USA)	Long-term value: 5 mg/m ³			
107-21-1 eth	anediol			
TWA (Italy)	Ceiling limit: 100 mg/m³ A4 (aerosol)			
VL (Italy)	Short-term value: 104 mg/m³, 40 ppm Long-term value: 52 mg/m³, 20 ppm Cute			
IOELV (EU)				
TLV (USA)				
WEEL (USA)) 1 (2)			
TWA (Italy PEL (USA REL (USA TLV (USA VL (Italy) IOELV (EU	 Regulatory information TWA (Italy): Valori Limite di Soglia (ACGIH) PEL (USA): Guide to Occupational Exposure Values (OSHA PELs) REL (USA): Guide to Occupational Exposure Values (NIOSH RELs) TLV (USA): Guide to Occupational Exposure Values (TLV) VL (Italy): D.Lgs. n. 81/2008 IOELV (EU): (EU) 2019/1831 WEEL (USA): Guide to Occupational Exposure Values (AIHA WEELs) 			
· DNELs		(
	enzoyl peroxide			
	NEL / Long term exposure - Systemic effects	2 mg/kg bw/d (general population)		
	NEL / Long term exposure - Systemic effects			
	NEL / Long term exposure - Local effects	0.034 mg/kg (workers)		
	NEL / Long term exposure - Systemic effects			
	131-11-3 dimethyl phthalate			
	NEL / Long term exposure - Systemic effects	9.4 ma/ka bw/d (general population)		
	NEL / Long term exposure - Systemic effects			
		135 mg/kg bw/d (workers)		
Inhalative D	NEL / Long term exposure - Systemic effects	16.3 mg/m³ (general population)		
		66.1 mg/m ³ (workers)		
107-21-1 eth	anediol			
	NEL / Long term exposure - Systemic effects	53 mg/kg bw/d (general population)		
	, , , , , , , , , , , , , , , , , , ,	106 mg/kg bw/d (workers)		
I		(Contd. on page		



Printing date 25.11.2022

Rev. n. 3

Revision: 25.11.2022

Page 5/12

Trade name: BPO paste PERVELOX EVO 50 - E02

(Contd. of page 4				
		7 mg/m³ (general population)		
		35 mg/m³ (workers)		
· PNECs	PNECs			
94-36-0 dibenzoy	94-36-0 dibenzoyl peroxide			
PNEC / aqua	0.00002 mg/l (freshwater)			
	0.000602 mg/l (intermittent releases)			
	0.000002 mg/l (marine water)			
PNEC / sediment	0.0127 mg/kg dw (freshwater)			
	0.00127 mg/kg dw (marine water)			
PNEC / soil	0.0025 mg/kg dw			
PNEC / STP	0.35 mg/l (sewage treatment plant)			
131-11-3 dimethy	l phthalate			
PNEC / aqua	0.192 mg/l (freshwater)			
	0.39 mg/l (intermittent releases)			
	0.0192 mg/l (marine water)			
PNEC / sediment	1.3 mg/kg dw (freshwater)			
	0.13 mg/kg dw (marine water)			
PNEC / soil	3.16 mg/kg dw			
PNEC / STP	4 mg/l (sewage treatment plant)			
107-21-1 ethaned	107-21-1 ethanediol			
PNEC / aqua	10 mg/l (freshwater)			
	10 mg/l (intermittent releases)			
	1 mg/l (marine water)			
PNEC / sediment	37 mg/kg dw (freshwater)			
	3.7 mg/kg dw (marine water)			
PNEC / soil	1.53 mg/kg dw			
PNEC / STP	199.5 mg/l (sewage treatment plant)			
Additional info	rmation: The lists valid during the maki	ing wore used as basis		

• Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working. The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

Meet hands before breaks and of the and of work

- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

• Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • **Material of gloves**

Neoprene gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.14 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.



Printing date 25.11.2022

Rev. n. 3

Revision: 25.11.2022

Trade name: BPO paste PERVELOX EVO 50 - E02

(Contd. of page 5)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. For the mixture of chemicals mentioned, the penetration time has to be at least 30 minutes (Permeation according to EN 374 Part 3: Level 2).

· Eye/face protection



Tightly sealed goggles

· Body protection: Light weight protective clothing

SECTION 9: Physical and chemical properties		
9.1 Information on basic physical and chemical properties		
· General Information		
· Physical state	Solid	
· Colour:	Different according to colouring	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
 Melting point/freezing point: 	0 °C	
Boiling point or initial boiling point and boiling range	Not applicable.	
	Prior to or during boiling decomposition occurs.	
· Flammability	May cause fire.	
· Lower and upper explosion limit		
· Lower:	Not applicable.	
Upper:	Not applicable.	
Flash point:	Not applicable.	
	Above the SADT value.	
· Decomposition temperature:	$SADT = 50 \ ^{\circ}C$	
	SADT: Self Accelerating Decomposition Temperature	
· pH at 20 °C	4-5	
· Viscosity:		
· Kinematic viscosity	172000-754000 m²/s	
· Dynamic:	(Brookfield, 20°C)	
Dynamic.	215000-867000 mPa·s	
· Solubility	215000-007000 mil a S	
· water:	Insoluble.	
	Not applicable.	
Partition coefficient n-octanol/water (log value) Vanour prossure:	Not applicable.	
 Vapour pressure: Density and/or relative density 	Not applicable.	
Density at 20 °C:	$1.15.1.25 a/cm^3$	
· Vapour density	1.15-1.25 g/cm³ Not applicable.	
· Particle characteristics	Pasty solid	
Particle characteristics	Pasiy soliu	
· 9.2 Other information		
· Appearance:		
· Form:	Pasty	
 Important information on protection of health and 		
environment, and on safety.		
 Auto-ignition temperature: 	Not applicable.	
 Explosive properties: 	Product does not present an explosion hazard.	
Change in condition		
· Evaporation rate	Not determined.	
· Information with regard to physical hazard classes		
· Explosives	Void	
· Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
· Flammable liquids	Void	
· Flammable solids	Void	
	(Contd. on page 7)	



Page 7/12

Printing date 25.11.2022

Rev. n. 3

Revision: 25.11.2022

Trade name: BPO paste PERVELOX EVO 50 - E02

		(Contd. of page 6)
 Self-reactive substances and mixtures 	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
 Self-heating substances and mixtures 	Void	
• Substances and mixtures, which emit flammable g	ases	
in contact with water	Void	
· Oxidising liquids	Void	
• Oxidising solids	Void	
· Organic peroxides		
Heating may cause a fire.		
· Corrosive to metals	Void	
 Desensitised explosives 	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- Exothermic thermal decomposition.

Visible decomposition with spontaneous ignition on heating.

 $SADT = 50^{\circ}C$

SADT (Self accelerating decomposition temperature) is the lowest temperature at which self accelerating decomposition may occur with a substance in the packaging as used in transport.

A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by thermal decomposition at and above the SADT.

Contact with incompatible substances can cause decomposition at or below the SADT.

· 10.3 Possibility of hazardous reactions

Reacts with reducing agents. Reacts with heavy metals. Reacts with alkali, amines and strong acids.

· 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

 10.6 Hazardous decomposition products: Benzoic acid Benzene Biphenyl Phenyl benzoate

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
94-36-0 di	94-36-0 dibenzoyl peroxide		
Oral LD0 >2,000 mg/kg (mouse) (OECD TG 401: Acute Oral Toxicity)			
Inhalative	LC0	24.3 mg/l (rat) (OECD TG 403: Acute Inhalation Toxicity)	
131-11-3 (131-11-3 dimethyl phthalate		
Oral	LD50	8,200 mg/kg (rat)	
Dermal	Dermal LD50 12,000 mg/kg (rabbit)		
107-21-1 e	ethanediol		
Oral	LD50	7,712 mg/kg (rat)	
Dermal	LD50	>3,500 mg/kg (rabbit)	
Inhalative	LC50 / 6h	>2.5 mg/l (mouse)	
· Skin cor	Skin corrosion/irritation Based on available data, the classification criteria are not met.		

· Serious eye damage/irritation

Causes serious eye irritation.

(Contd. of page 7)

Safety data sheet (English translation without any country-specific legislation) according to 1907/2006/EC, Article 31

Printing date 25.11.2022

RAICHEM

Rev. n. 3

Revision: 25.11.2022

Trade name: BPO paste PERVELOX EVO 50 - E02

· Respiratory or skin sensitisation

- May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxici	tv:		
94-36-0 dibenzo			
LC50 / 96h	0.0602 mg/l (fish - Oncorhynchus mykiss) (OECD TG 203: Fish, Acute Toxicity Test)		
EC50 / 48h 0.11 mg/l (crustacea - Daphnia magna) (OECD TG 202: Daphnia sp. Acute Immobilisation Test)			
	ErC50 / 72h 0.0711 mg/l (algae - Pseudokirchneriella subcapitata) (OECD TG 201: Alga, Growth Inhibition Test)		
M Factor Acute	10 0.0216 mg/l (figh Organity Tagt) (OECD TO 202; Figh Aguta Tayinity Tagt)		
NOEC / 96h	0.0316 mg/l (fish - Oncorhynchus mykiss) (OECD TG 203: Fish, Acute Toxicity Test)		
EC10 / 21d	0.001 mg/l (crustacea - Daphnia magna) (OECD TG 211: Daphnia magna Reproduction Test)		
NOEC / 72 h	0.02 mg/l (algae - Pseudokirchneriella subcapitata) (OECD TG 201: Alga, Growth Inhibition Test)		
M Factor Chroni			
131-11-3 dimet			
LC50 / 96h	39 mg/l (fish - Pimephales promelas)		
EC50 / 48h	>52 mg/l (crustacea - Daphnia magna)		
ErC50 / 72h	259.76 mg/l (algae - Scenedesmus subspicatus)		
NOEC / 21d	9.6 mg/l (crustacea - Daphnia magna)		
107-21-1 ethane			
LC50 / 96h	72,860 mg/l (fish - Pimephales promelas)		
EC50 / 48h	>100 mg/l (crustacea - Daphnia magna) (OECD TG 202: Daphnia sp. Acute Immobilisation Test)		
ErC50 / 96h	6,500-13,000 mg/l (algae - Pseudokirchneriella subcapitata)		
NOEC / 7d	8,590 mg/l (crustacea - Ceriodaphnia dubia)		
· 12.2 Persistenc	e and degradability		
94-36-0 dibenzo	pyl peroxide		
Ready Biodegra	dability in water / 28d 71 % (OECD TG 301 D: Ready Biodegradability: Closed Bottle Test)		
131-11-3 dimetl	hyl phthalate		
Ready Biodegra	dability in water / 11d 91 % (OECD TG 301 E: Ready biodegradability: Modified OECD Screening Test)		
107-21-1 ethane	ediol		
Ready Biodegra	dability in water / 10d 90-100 % (OECD TG 301A: Ready Biodegradability: DOC Die Away Test)		
· 12.3 Bioaccum	ulative potential		
94-36-0 dibenzo	byl peroxide		
	2°C) (OECD TG 117: Partition Coefficient (n-octanol / water), HPLC Method))		
131-11-3 dimetl	hyl phthalate		
Log Kow 1.54 /(25°C) (OECD TG 107: Partition Coefficient (n-octanol / water), Shake Flask Method)			
BCF 57 /21d (fish - Lepomis macrochirus)			
12.4 Mobility in	soil		
94-36-0 dibenzo			
	2°C) (OECD TG 121: (Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using erformance Liquid Chromatography (HPLC))		
	(Contd. on page		



Printing date 25.11.2022

Rev. n. 3

Revision: 25.11.2022

Trade name: BPO paste PERVELOX EVO 50 - E02

(Contd. of page 8)

131-11-3 dimethyl phthalate

Log Koc 1.5

- · 12.5 Results of PBT and vPvB assessment
 - **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· Remark: Very toxic for fish

• Additional ecological information:

· General notes:

Also poisonous for fish and plankton in water bodies. Very toxic for aquatic organisms Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport informati	ion
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3108
 14.2 UN proper shipping name ADR 	ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide ENVIRONMENTALLY HAZARDOUS
· IMDG, IATA	ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)
· 14.3 Transport hazard class(es)	
ADR	
· Class · Label	5.2 Organic peroxides. 5.2
· IMDG, IATA	
· Class	5.2 Organic peroxides.
· Label	5.2
· 14.4 Packing group	
· ADR, IMDĞ, IATA	Void
· 14.5 Environmental hazards:	
• Marine pollutant:	Yes
Special marking (ADR):	Symbol (fish and tree)



Page 10/12

(Contd of page 9)

Safety data sheet (English translation without any country-specific legislation)

according to 1907/2006/EC, Article 31

Printing date 25.11.2022

Rev. n. 3

Revision: 25.11.2022

Trade name: BPO paste PERVELOX EVO 50 - E02

	(Cond. of page s
14.6 Special precautions for user	Warning: Organic peroxides.
Hazard identification number (Kemler code):	-
EMS Number:	F-J,S-R
· Stowage Category	D
· Stowage Code	SW1 Protected from sources of heat.
· Segregation Code	SG35 Stow "separated from" SGG1-acids
	SG36 Stow "separated from" SGG18-alkalis.
	SG72 See 7.2.6.3.2.
14.7 Maritime transport in bulk according to IMC)
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	500 g
· Transport category	2
· Tunnel restriction code	D
·IMDG	
· Limited quantities (LQ)	500 g
· UN "Model Regulation":	UN 3108 ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOY) PEROXIDE), 5.2, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Regulation (EC) No 1907/2006 (REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals) Regulation (EC) No 1272/2008 (CLP - Classification, Labelling and Packaging of substances and mixtures) Compilation of Safety Data Sheet: Reg.UE n. 878/2020 (amending Reg.EC n.1907/2006, Annex II)

· Directive 2012/18/EU (Seveso)

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

REGULATION (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

• Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has been carried out for Dibenzoyl peroxide - CAS 94-36-0

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Page 11/12

Safety data sheet (English translation without any country-specific legislation) according to 1907/2006/EC, Article 31

Printing date 25.11.2022

RAICHEM

Rev. n. 3

Revision: 25.11.2022

Trade name: BPO paste PERVELOX EVO 50 - E02

(Contd. of page 10) · Relevant phrases H241 Heating may cause a fire or explosion. H302 Harmful if swallowed. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. Classification according to Regulation (EC) No 1272/2008 Organic peroxides Expert judgement Serious eye damage/eye irritation The classification of the mixture is generally based on the Skin sensitisation calculation method using substance data according to Hazardous to the aquatic environment - short-term (acute) Regulation (EC) No 1272/2008. aquatic hazard Hazardous to the aquatic environment - long-term (chronic) aquatic hazard · (+1.2) Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU9 Manufacture of fine chemicals SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys) SU12 Manufacture of plastics products, including compounding and conversion SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Process category PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC5 Mixing or blending in batch processes PROC7 Industrial spraving PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC10 Roller application or brushing PROC11 Non industrial spraying PROC13 Treatment of articles by dipping and pouring PROC14 Tabletting, compression, extrusion, pelletisation, granulation PROC19 Manual activities involving hand contact PROC21 Low energy manipulation and handling of substances bound in/on materials or articles · Environmental release category ERC2 Formulation into mixture ERC6d Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article) ERC8b Widespread use of reactive processing aid (no inclusion into or onto article, indoor) ERC8e Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) · Contact: Raichem S.p.A. • Version number of previous version: 2 Abbreviations and acronyms: REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals GHS: Globally Harmonised System of Classification and Labelling of Chemicals IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) CLP: Classification, Labelling and Packaging TLV: Threshold Limit Value TLV-TWA: Threshold Limit Value - Time Weighted Average TLV-STEL: Threshold Limit Value - Short Term Exposure Limit PEL: Permissible Exposure Limits (Limiti di esposizione consentiti) REL: Recommended Exposure Limits (Limiti di esposizione raccomandati) IOELV: Indicative Occupational Exposure Limit Value WEELs: Workplace Environmental Exposure Limits (Limiti di esposizione ambientale sul posto di lavoro) BEI: Biological Exposure Indices LD50: Lethal dose, 50 percent LC50: Lethal Concentration, 50 percent

- Kow: Octanol-Water partition coefficient Koc: Organic Carbon partition Coefficient
- BCF: BioConcentration Factor



Printing date 25.11.2022

RAICHEM

Rev. n. 3

Revision: 25.11.2022

Trade name: BPO paste PERVELOX EVO 50 - E02

(Contd. of page 11) LC50: LC50: Lethal Concentration, 50 percent EC50: Effective Concentration, 50 percent EC10: Effective Concentration, 10 percent ErC50: Effective Concentration, 50 percent, growth rate NOEC: No-Observed Effect Concentration. WGK: Wassergefährdungsklasse - Water hazard class [Germany] ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Org. Perox. B: Organic peroxides – Type B Org. Perox. E: Organic peroxides – Type E/F Acute Tox. 4: Acute toxicity - Category 4 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 • * Data compared to the previous version altered. EU