This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



#### **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** EPOXY FILLER FIBREGLASS 2:1 NEW

Other means of identification:

UFI: ESS2-U189-S00P-MUPX

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Products for ships, boats,  $\dots$  (construction, repair,  $\dots$ )

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Troton Sp. z o.o. Ząbrowo 14A

78-120 Gościno - Zachodniopomorskie - Polska Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22

troton@troton.com.pl www.troton.pl / www.troton.eu

**1.4 Emergency telephone number:** (8am-4pm)+48 094 35 123 94; 112

# **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture:

#### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Irrit. 2: Eye irritation, Category 2, H319 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1: Sensitisation, skin, Category 1, H317

# 2.2 Label elements:

#### CLP Regulation (EC) No 1272/2008:

#### Warning



#### **Hazard statements:**

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1:  $\mbox{H317}$  -  $\mbox{May}$  cause an allergic skin reaction.

#### **Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

#### **Supplementary information:**

EUH205: Contains epoxy constituents. May produce an allergic reaction.

EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### Substances that contribute to the classification

Bis-[4-(2,3-epoxipropoxi)phenyl]propane; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol; 1,6-bis(2,3-epoxypropoxy)hexane

#### 2.3 Other hazards:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



#### **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

# SECTION 2: HAZARDS IDENTIFICATION (continued)

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

|   | Identification   |  | Chemical name/Classification  |                 |            |  |  |  |
|---|--|--|---|-----------------|------------|--|--|--|
| CAS:  | 1675-54-3  | Bis-[4-(2,3-epoxipro                         | poxi)phenyl]propane <sup>(1)</sup>  | ATP CLP00       |            |  |  |  |
|   | 216-823-5<br>603-073-00-2<br>01-2119456619-26-<br>XXXX   | Regulation 1272/2008                         | Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning               | •               | 10 - <25 % |  |  |  |
| CAS:  | 7727-43-7  | Barium Sulfate(2)                            |   | Not classified  |            |  |  |  |
|   | 231-784-4<br>Non-applicable<br>01-2119491274-35-<br>XXXX | Regulation 1272/2008                         |   |                 | 10 - <25 % |  |  |  |
| CAS:<br>EC:   | 9003-36-5<br>500-006-8                                   | Formaldehyde, oligo<br>phenol <sup>(1)</sup> | meric reaction products with 1-chloro-2,3-epoxypropane and                          | Self-classified |            |  |  |  |
| Index: Non-applicable<br>REACH: 01-2119454392-40-<br>XXXX |  | Regulation 1272/2008                         | Aquatic Chronic 2: H411; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning          | (Î) (Î)         | 10 - <25 % |  |  |  |
| CAS:<br>EC:   | 16096-31-4<br>240-260-4                                  | 1,6-bis(2,3-epoxypro                         | ppoxy)hexane <sup>(1)</sup>   | Self-classified |            |  |  |  |
| Index:  | Non-applicable<br>01-2119463471-41-<br>XXXX              | Regulation 1272/2008                         | Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H31 | 7 - Warning 😲   | 5 - <10 %  |  |  |  |
| CAS:<br>EC:   | 13463-67-7   | Titanium dioxide (ae                         | rodynamic diameter ≤ 10 μm) <sup>(1)</sup>  | Self-classified |            |  |  |  |
| Index:  | 236-675-5<br>Non-applicable<br>01-2119489379-17-<br>XXXX | Regulation 1272/2008                         | Carc. 2: H351 - Warning   |                 | 1 - <2,5 % |  |  |  |
| CAS:  | 14808-60-7   | Quartz (1 %< RCS <                           | 10%)(2)   | Self-classified |            |  |  |  |
| EC:<br>Index:<br>REACH:                                   | 238-878-4<br>Non-applicable<br>Non-applicable            | Regulation 1272/2008                         | STOT RE 2: H373 - Warning   | <b>&amp;</b>    | <1 %       |  |  |  |

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

#### Other information:

| Identification | Specific concentration limit  |
|----------------|---|
|                | % (w/w) >=5: Skin Irrit. 2 - H315<br>% (w/w) >=5: Eye Irrit. 2 - H319 |

# **SECTION 4: FIRST AID MEASURES**

# 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

#### By skin contact:

<sup>(2)</sup> Substance with a Union workplace exposure limit

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



#### **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

# SECTION 4: FIRST AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

# **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media:

#### Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

# Unsuitable extinguishing media:

Non-applicable

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

# 6.1 Personal precautions, protective equipment and emergency procedures:

# For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

# For emergency responders:

See section 8.

#### **6.2** Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

#### 6.3 Methods and material for containment and cleaning up:

It is recommended:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



#### **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

# SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

#### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

#### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 10 °C

Maximum Temp.: 25 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| 20) 2025/ 2001:         |                              |  |                       |  |  |  |  |
|-------------------------|------------------------------|--|-----------------------|--|--|--|--|
| Identification          | Occupational exposure limits |  |                       |  |  |  |  |
| Barium Sulfate          | IOELV (8h)                   |  | 0,5 mg/m <sup>3</sup> |  |  |  |  |
| CAS: 7727-43-7          | IOELV (STEL)                 |  |                       |  |  |  |  |
| Quartz (1 %< RCS < 10%) | IOELV (8h)                   |  | 0,1 mg/m <sup>3</sup> |  |  |  |  |
| CAS: 14808-60-7         | IOELV (STEL)                 |  |                       |  |  |  |  |

# **DNEL (Workers):**

|   |            | Short exposure |                | Long exposure          |                |
|---|------------|----------------|----------------|------------------------|----------------|
| Identification                          |            | Systemic       | Local          | Systemic               | Local          |
| Bis-[4-(2,3-epoxipropoxi)phenyl]propane | Oral       | Non-applicable | Non-applicable | Non-applicable         | Non-applicable |
| CAS: 1675-54-3                          | Dermal     | Non-applicable | Non-applicable | 0,75 mg/kg             | Non-applicable |
| EC: 216-823-5                           | Inhalation | Non-applicable | Non-applicable | 4,93 mg/m <sup>3</sup> | Non-applicable |

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



# **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

|  |            | Short exposure          |                | Long exposure           |                        |
|--|------------|-------------------------|----------------|-------------------------|------------------------|
| Identification   |            | Systemic                | Local          | Systemic                | Local                  |
| Barium Sulfate   | Oral       | Non-applicable          | Non-applicable | Non-applicable          | Non-applicable         |
| CAS: 7727-43-7   | Dermal     | Non-applicable          | Non-applicable | Non-applicable          | Non-applicable         |
| EC: 231-784-4  | Inhalation | Non-applicable          | Non-applicable | 10 mg/m <sup>3</sup>    | 10 mg/m <sup>3</sup>   |
| Formaldehyde, oligomeric reaction products with 1-chloro-<br>2,3-epoxypropane and phenol | Oral       | Non-applicable          | Non-applicable | Non-applicable          | Non-applicable         |
| CAS: 9003-36-5   | Dermal     | Non-applicable          | Non-applicable | 104,15 mg/kg            | Non-applicable         |
| EC: 500-006-8  | Inhalation | Non-applicable          | Non-applicable | 29,39 mg/m <sup>3</sup> | Non-applicable         |
| 1,6-bis(2,3-epoxypropoxy)hexane  | Oral       | Non-applicable          | Non-applicable | Non-applicable          | Non-applicable         |
| CAS: 16096-31-4  | Dermal     | Non-applicable          | Non-applicable | 6 mg/kg                 | Non-applicable         |
| EC: 240-260-4  | Inhalation | 10,57 mg/m <sup>3</sup> | Non-applicable | 10,57 mg/m <sup>3</sup> | 0,44 mg/m <sup>3</sup> |

# **DNEL (General population):**

|  |            | Short e                | xposure        | Long exposure          |                        |
|--|------------|------------------------|----------------|------------------------|------------------------|
| Identification   |            | Systemic               | Local          | Systemic               | Local                  |
| Bis-[4-(2,3-epoxipropoxi)phenyl]propane  | Oral       | Non-applicable         | Non-applicable | 0,5 mg/kg              | Non-applicable         |
| CAS: 1675-54-3   | Dermal     | Non-applicable         | Non-applicable | 0,0893 mg/kg           | Non-applicable         |
| EC: 216-823-5  | Inhalation | Non-applicable         | Non-applicable | 0,87 mg/m <sup>3</sup> | Non-applicable         |
| Barium Sulfate   | Oral       | Non-applicable         | Non-applicable | 13000 mg/kg            | Non-applicable         |
| CAS: 7727-43-7   | Dermal     | Non-applicable         | Non-applicable | Non-applicable         | Non-applicable         |
| EC: 231-784-4  | Inhalation | Non-applicable         | Non-applicable | 10 mg/m <sup>3</sup>   | Non-applicable         |
| Formaldehyde, oligomeric reaction products with 1-chloro-<br>2,3-epoxypropane and phenol | Oral       | Non-applicable         | Non-applicable | 6,25 mg/kg             | Non-applicable         |
| CAS: 9003-36-5   | Dermal     | Non-applicable         | Non-applicable | 62,5 mg/kg             | Non-applicable         |
| EC: 500-006-8  | Inhalation | Non-applicable         | Non-applicable | 8,7 mg/m <sup>3</sup>  | Non-applicable         |
| 1,6-bis(2,3-epoxypropoxy)hexane  | Oral       | 1,5 mg/kg              | Non-applicable | 1,5 mg/kg              | Non-applicable         |
| CAS: 16096-31-4  | Dermal     | 1,7 mg/kg              | Non-applicable | 3 mg/kg                | Non-applicable         |
| EC: 240-260-4  | Inhalation | 5,29 mg/m <sup>3</sup> | Non-applicable | 5,29 mg/m <sup>3</sup> | 0,27 mg/m <sup>3</sup> |

# PNEC:

| Identification   |              |                |                         |                |
|--|--------------|----------------|-------------------------|----------------|
| Bis-[4-(2,3-epoxipropoxi)phenyl]propane  | STP          | 10 mg/L        | Fresh water             | 0,006 mg/L     |
| CAS: 1675-54-3   | Soil         | 0,065 mg/kg    | Marine water            | 0,001 mg/L     |
| EC: 216-823-5  | Intermittent | 0,018 mg/L     | Sediment (Fresh water)  | 0,341 mg/kg    |
|  | Oral         | 0,011 g/kg     | Sediment (Marine water) | 0,034 mg/kg    |
| Barium Sulfate   | STP          | 62,2 mg/L      | Fresh water             | 0,115 mg/L     |
| CAS: 7727-43-7   | Soil         | 207,7 mg/kg    | Marine water            | Non-applicable |
| EC: 231-784-4  | Intermittent | Non-applicable | Sediment (Fresh water)  | 600,4 mg/kg    |
|  | Oral         | Non-applicable | Sediment (Marine water) | Non-applicable |
| Formaldehyde, oligomeric reaction products with 1-chloro-<br>2,3-epoxypropane and phenol | STP          | 10 mg/L        | Fresh water             | 0,003 mg/L     |
| CAS: 9003-36-5   | Soil         | 0,237 mg/kg    | Marine water            | 0 mg/L         |
| EC: 500-006-8  | Intermittent | 0,025 mg/L     | Sediment (Fresh water)  | 0,294 mg/kg    |
|  | Oral         | Non-applicable | Sediment (Marine water) | 0,029 mg/kg    |
| 1,6-bis(2,3-epoxypropoxy)hexane  | STP          | 1 mg/L         | Fresh water             | 0,011 mg/L     |
| CAS: 16096-31-4  | Soil         | 0,223 mg/kg    | Marine water            | 0,001 mg/L     |
| EC: 240-260-4  | Intermittent | 0,115 mg/L     | Sediment (Fresh water)  | 0,283 mg/kg    |
|  | Oral         | Non-applicable | Sediment (Marine water) | 0,028 mg/kg    |

#### 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



# **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

#### B.- Respiratory protection

| Pict           | togram                 | PPE  | Labelling | CEN Standard  | Remarks  |
|----------------|------------------------|--|-----------|---|--|
| Mar<br>respira | ndatory<br>atory tract | Filter mask for gases and vapours (Filter type: A)                     | CAT III   | EN 405:2002+A1:2010   | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |
| Mar<br>respira | ndatory<br>atory tract | Filter mask for gases,<br>vapours and particles (Filter<br>type: FFP3) | CAT III   | EN 149:2001+A1:2009<br>EN 405:2002+A1:2010<br>EN ISO 136:1998 | Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.  |

# C.- Specific protection for the hands

| Pictogram                 | PPE   | Labelling | CEN Standard  | Remarks  |
|---------------------------|---|-----------|---|--|
| Mandatory hand protection | NON-disposable chemical<br>protective gloves (Material:<br>Nitrile, Breakthrough time: ><br>480 min, Thickness: 0.4 mm) |           | EN ISO 374-1:2016+A1:2018<br>EN 16523-1:2015+A1:2018<br>EN 420:2004+A1:2010 | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

#### D.- Ocular and facial protection

| Pictogram                 | PPE  | Labelling | CEN Standard                    | Remarks   |
|---------------------------|--|-----------|---------------------------------|---|
| Mandatory face protection | Panoramic glasses against<br>splash/projections. | CATII     | EN 166:2002<br>EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

# E.- Body protection

| Pictogram                          | PPE  | Labelling | CEN Standard  | Remarks   |
|------------------------------------|--|-----------|---|---|
| Mandatory complete body protection | Disposable clothing for<br>protection against chemical<br>risks, with antistatic and<br>fireproof properties | CAT III   | EN 1149-1,2,3<br>EN 13034:2005+A1:2009<br>EN ISO 13982-<br>1:2004/A1:2010<br>EN ISO 6529:2013<br>EN ISO 6530:2005<br>EN ISO 13688:2013<br>EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
| Mandatory foot protection          | Safety footwear for<br>protection against chemical<br>risk, with antistatic and heat<br>resistant properties | CAT III   | EN ISO 13287:2013<br>EN ISO 20345:2011<br>EN 13832-1:2019   | Replace boots at any sign of deterioration.   |

#### F.- Additional emergency measures

| Emergency measure                       | Standards                                       | Emergency measure | Standards                                      |
|---|---|-------------------|--|
| +++++++++++++++++++++++++++++++++++++++ | ANSI Z358-1<br>ISO 3864-1:2011, ISO 3864-4:2011 | <b>⊢</b>          | DIN 12 899<br>ISO 3864-1:2011, ISO 3864-4:2011 |
| Emergency shower                        |   | Eyewash stations  |  |

#### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

\*Not relevant due to the nature of the product, not providing information property of its hazards.

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



# **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

| SECI | ION 9: PHYSICAL AND CHEMICAL PROPERTIES  | s (continued)           |  |  |  |  |  |
|------|--|-------------------------|--|--|--|--|--|
| 9.1  | Information on basic physical and chemical properties:   |                         |  |  |  |  |  |
|      | For complete information see the product datasheet.  |                         |  |  |  |  |  |
|      | Appearance:  |                         |  |  |  |  |  |
|      | Physical state at 20 °C:   | Liquid                  |  |  |  |  |  |
|      | Appearance:  | Viscous                 |  |  |  |  |  |
|      | Colour:  | White                   |  |  |  |  |  |
|      | Odour:   | Characteristic          |  |  |  |  |  |
|      | Odour threshold:   | Non-applicable *        |  |  |  |  |  |
|      | Volatility:  |                         |  |  |  |  |  |
|      | Boiling point at atmospheric pressure:   | 100 °C                  |  |  |  |  |  |
|      | Vapour pressure at 20 °C:  | 2350 Pa                 |  |  |  |  |  |
|      | Vapour pressure at 50 °C:  | 12381,01 Pa (12,38 kPa) |  |  |  |  |  |
|      | Evaporation rate at 20 °C:   | Non-applicable *        |  |  |  |  |  |
|      | Product description:   |                         |  |  |  |  |  |
|      | Density at 20 °C:  | 1500 kg/m³              |  |  |  |  |  |
|      | Relative density at 20 °C:   | Non-applicable *        |  |  |  |  |  |
|      | Dynamic viscosity at 20 °C:  | Non-applicable *        |  |  |  |  |  |
|      | Kinematic viscosity at 20 °C:  | Non-applicable *        |  |  |  |  |  |
|      | Kinematic viscosity at 40 °C:  | >20,5 mm²/s             |  |  |  |  |  |
|      | Concentration:   | Non-applicable *        |  |  |  |  |  |
|      | pH:  | Non-applicable *        |  |  |  |  |  |
|      | Vapour density at 20 °C:   | Non-applicable *        |  |  |  |  |  |
|      | Partition coefficient n-octanol/water 20 °C:   | Non-applicable *        |  |  |  |  |  |
|      | Solubility in water at 20 °C:  | Non-applicable *        |  |  |  |  |  |
|      | Solubility properties:   | Non-applicable *        |  |  |  |  |  |
|      | Decomposition temperature:   | Non-applicable *        |  |  |  |  |  |
|      | Melting point/freezing point:  | Non-applicable *        |  |  |  |  |  |
|      | Flammability:  |                         |  |  |  |  |  |
|      | Flash Point:   | Non Flammable (>60 °C)  |  |  |  |  |  |
|      | Flammability (solid, gas):   | Non-applicable *        |  |  |  |  |  |
|      | Autoignition temperature:  | Non-applicable *        |  |  |  |  |  |
|      | Lower flammability limit:  | Non-applicable *        |  |  |  |  |  |
|      | Upper flammability limit:  | Non-applicable *        |  |  |  |  |  |
|      | Particle characteristics:  |                         |  |  |  |  |  |
|      | Median equivalent diameter:  | Non-applicable          |  |  |  |  |  |
| 9.2  | Other information:   |                         |  |  |  |  |  |
|      | Information with regard to physical hazard class   |                         |  |  |  |  |  |
|      | Explosive properties:  | Non-applicable *        |  |  |  |  |  |
|      | Oxidising properties:  | Non-applicable *        |  |  |  |  |  |
|      | Corrosive to metals:   | Non-applicable *        |  |  |  |  |  |
|      | Heat of combustion:  | Non-applicable *        |  |  |  |  |  |
|      | Aerosols-total percentage (by mass) of flammable components:                                       | Non-applicable *        |  |  |  |  |  |
|      | Other safety characteristics:  |                         |  |  |  |  |  |
|      | Surface tension at 20 °C:  | Non-applicable *        |  |  |  |  |  |
|      | *Not relevant due to the nature of the product, not providing information property of its hazards. |                         |  |  |  |  |  |

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



#### **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Refraction index: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

#### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

#### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight       | Humidity       |
|--------------------|------------------|-------------------------|----------------|----------------|
| Not applicable     | Not applicable   | Not applicable          | Not applicable | Not applicable |

#### 10.5 Incompatible materials:

| Acids              | Water  | Oxidising materials | Combustible materials | Others                        |
|--------------------|--|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | g acids Not applicable Not applicable Not appl |                     | Not applicable        | Avoid alkalis or strong bases |

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

# **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# SEA

#### **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.

IARC: Bis-[4-(2,3-epoxipropoxi)phenyl]propane (3); Talc (3); Titanium dioxide (aerodynamic diameter  $\leq$  10  $\mu$ m) (2B); Quartz (1 % < RCS < 10%) (1)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### Other information:

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter  $\leq 10~\mu m$ ): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10~\mu m$ 

#### Specific toxicology information on the substances:

| Identification   | Acute toxicity  |                | Genus  |
|--|-----------------|----------------|--------|
| Bis-[4-(2,3-epoxipropoxi)phenyl]propane  | LD50 oral       | >2000 mg/kg    |        |
| CAS: 1675-54-3   | LD50 dermal     | 20000 mg/kg    | Rabbit |
| EC: 216-823-5  | LC50 inhalation | >5 mg/L        |        |
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | LD50 oral       | >2000 mg/kg    |        |
| CAS: 9003-36-5   | LD50 dermal     | >2000 mg/kg    |        |
| EC: 500-006-8  | LC50 inhalation | >20 mg/L       |        |
| 1,6-bis(2,3-epoxypropoxy)hexane  | LD50 oral       | >2000 mg/kg    |        |
| CAS: 16096-31-4  | LD50 dermal     | >2000 mg/kg    |        |
| EC: 240-260-4  | LC50 inhalation | Non-applicable |        |
| Titanium dioxide (aerodynamic diameter ≤ 10 μm)                                      | LD50 oral       | 10000 mg/kg    | Rat    |
| CAS: 13463-67-7  | LD50 dermal     | 10000 mg/kg    | Rabbit |
| EC: 236-675-5  | LC50 inhalation | >5 mg/L        |        |
| Barium Sulfate   | LD50 oral       | >5000 mg/kg    | Rat    |
| CAS: 7727-43-7   | LD50 dermal     | >2000 mg/kg    |        |
| EC: 231-784-4  | LC50 inhalation | >5 mg/L        |        |
| Quartz (1 %< RCS < 10%)  | LD50 oral       | >2000 mg/kg    |        |
| CAS: 14808-60-7  | LD50 dermal     | >2000 mg/kg    |        |
| EC: 238-878-4  | LC50 inhalation | >5 mg/L        |        |

# 11.2 Information on other hazards:

# **Endocrine disrupting properties**

Endocrine-disrupting properties: The product fails to meet the criteria.

## Other information

Non-applicable

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



#### **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

# SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

#### 12.1 Toxicity:

#### **Acute toxicity:**

| Identification   | Concentration |                   | Species         | Genus      |
|--|---------------|-------------------|-----------------|------------|
| Barium Sulfate   | LC50          | 76000 mg/L (96 h) | Salmo gairdneri | Fish       |
| CAS: 7727-43-7   | EC50          | Non-applicable    |                 |            |
| EC: 231-784-4  | EC50          | Non-applicable    |                 |            |
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | LC50          | >1 - 10 (96 h)    |                 | Fish       |
| CAS: 9003-36-5   | EC50          | >1 - 10 (48 h)    |                 | Crustacean |
| EC: 500-006-8  | EC50          | >1 - 10 (72 h)    |                 | Algae      |
| 1,6-bis(2,3-epoxypropoxy)hexane  | LC50          | >10 - 100 (96 h)  |                 | Fish       |
| CAS: 16096-31-4  | EC50          | >10 - 100 (48 h)  |                 | Crustacean |
| EC: 240-260-4  | EC50          | >10 - 100 (72 h)  |                 | Algae      |

#### **Chronic toxicity:**

| Identification               | Concentration |                | Species     | Genus |
|------------------------------|---------------|----------------|-------------|-------|
| Barium Sulfate               | NOEC          | 100 mg/L       | Danio rerio | Fish  |
| CAS: 7727-43-7 EC: 231-784-4 | NOEC          | Non-applicable |             |       |

#### 12.2 Persistence and degradability:

Not available

#### 12.3 Bioaccumulative potential:

Not available

# 12.4 Mobility in soil:

Not available

#### 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

# 12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

# 12.7 Other adverse effects:

Not described

# SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods:

| Code                   | Description  | Waste class (Regulation (EU) No<br>1357/2014) |
|------------------------|--|---|
| 08 01 11*<br>15 01 10* | waste paint and varnish containing organic solvents or other hazardous substances packaging containing residues of or contaminated by hazardous substances | Dangerous                                     |

#### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



#### **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

# SECTION 14: TRANSPORT INFORMATION

#### Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



14.1 UN number or ID number: UN3082

14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Formaldehyde, oligomeric reaction products with 1-chloro-2,3-

epoxypropane and phenol)

14.3 Transport hazard class(es):

9 Labels:

III 14.4 Packing group: 14.5 Environmental hazards: Yes

14.6 Special precautions for user

Special regulations: 274, 335, 375, 601

Tunnel restriction code:

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Maritime transport in bulk

according to IMO instruments:

Non-applicable

#### Transport of dangerous goods by sea:

With regard to IMDG 39-18:

14.1 UN number or ID number: UN3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 14.2 UN proper shipping name:

(Formaldehyde, oligomeric reaction products with 1-chloro-2,3-

epoxypropane and phenol)

14.3 Transport hazard class(es):

9 Labels:

14.4 Packing group: III 14.5 Marine pollutant: Yes

14.6 Special precautions for user

Special regulations: 335, 969, 274 EmS Codes: F-A, S-F see section 9 Physico-Chemical properties:

5 L Limited quantities:

Non-applicable Segregation group: 14.7 Maritime transport in bulk

according to IMO instruments:

Non-applicable

# Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:



14.1 UN number or ID number: UN3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 14.2 UN proper shipping name:

(Formaldehyde, oligomeric reaction products with 1-chloro-2,3-

epoxypropane and phenol)

14.3 Transport hazard class(es):

9 Labels: III 14.4 Packing group: 14.5 Environmental hazards: Yes

14.6 Special precautions for user

see section 9 Physico-Chemical properties: 14.7 Maritime transport in bulk

according to IMO

instruments:

Non-applicable

# **SECTION 15: REGULATORY INFORMATION**

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



#### **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

#### SECTION 15: REGULATORY INFORMATION (continued)

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

#### Seveso III:

Non-applicable

# Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

# SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

#### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

#### Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H412: Harmful to aquatic life with long lasting effects.

H319: Causes serious eye irritation.

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### CLP Regulation (EC) No 1272/2008:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Carc. 2: H351 - Suspected of causing cancer (Inhalation).

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).

#### Classification procedure:

Skin Irrit. 2: Calculation method Skin Sens. 1: Calculation method Aquatic Chronic 3: Calculation method Eye Irrit. 2: Calculation method

#### Advice related to training:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



#### **EPOXY FILLER FIBREGLASS 2:1 NEW**

Printing: 30/05/2022 Date of compilation: 19/12/2017 Revised: 23/05/2022 Version: 4 (Replaced 3)

# SECTION 16: OTHER INFORMATION (continued)

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

# Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

#### **Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

ICAO: International Civil Aviation Organisation

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.