

TECHNICAL DATA SHEET

S9 PRO CUT

Polishing Liquid Compound



PRODUCT DESCRIPTION

S9 PRO CUT polishing compound has been developed for effective polishing of both white and dark gelcoats. It performs exceptionally well when used with conventional rotary and pneumatic machines, ensuring high efficiency. The product is designed for use after sanding with abrasive paper of P800 grit and above. It guarantees fast and effective scratch removal while delivering a high-gloss finish.

This is a professional solution intended for demanding finishing applications.

PRODUCT INFORMATION

SURFACE TYPE	white and dark gelcoat (laminate), hard industrial paints		
EFFECT	removal of deep sanding scratches from hard surfaces and enhancement of gloss level		
CATEGORY	professional users, manufacturing facilities		
PRODUCT TYPE	Two-step process (two polishing pads – hard and soft) 1. hard pad + S9 compound – fast removal of deep sanding scratches, low gloss level 2. soft pad + S9 compound (optional) – removal of polishing swirls and haze, enhancement of gloss level 3. Soft wool pad + S1 / S1 PREMIUM compound – removal of holograms, elimination of micro-scratches, increased gloss level.		
COLOR	white		
DENSITY	1,27 kg/l		
CONSISTENCY	paste		
METHODE OF POLISHING	machine		
MACHINE TYPE	rotary machine		
APPLICATOR	sheep wool, lambswool, hard sponges		
CUT LEVEL		10/10	
GLOSS LEVEL		7/10	

INSTRUCTION FOR USE

SURFACE PREPARATION	Clean the surface to be polished with S3 liquid. If defect removal is necessary, finish sanding the surface with abrasive paper of at least the following grit: • Gelcoat (finished products, light and dark colors): minimum P800 or finer • Paints: minimum P1200 or finer Remove sanding dust. Clean the surface again.
INSTRUCTION	Apply S9 PRO CUT compound to the part or polishing pad (sheep wool). Spread the compound over the entire surface at low speed (800–1000 RPM), polishing until the compound changes consistency. Gradually increase the speed up to a maximum of 1800 RPM; if deeper scratches need to be removed, apply light pressure on the pad. Polish until defects are eliminated and a high gloss is achieved. Remove any remaining compound using a microfiber cloth. If necessary, repeat the polishing process.

TECHNICAL DATA SHEET

S9 PRO CUT

Polishing Liquid Compound



FINISHING	To remove polishing swirls, haze, and to enhance gloss level, especially after using S9 PRO CUT on dark colors, you can use: • Sea-Line® S9 PRO CUT + lambswool / polishing sponge • Sea-Line® S1 / S1 PREMIUM + lambswool
FURTHER WORK	For surface protection, it is recommended to use: • Sea-Line® S4 WAX or Sea-Line® S5 QUICK WAX
IMPORTANT NOTES	The factors influencing the final result include: • Proper surface preparation by selecting the appropriate sandpaper grit • Type of applicator used For more details, visit www.sea-line.eu.
STORAGE AND SAFETY INFORMATION	
SHELF LIFE	24 months from production date
STORAGE	Product components should be stored in tightly sealed containers, in a temperature of 10-25°C, away from sources of fire, heat and sunlight. Close container tightly immediately after each use. Store in a dry place and keep the cans sealed until use. Keep away from children. Protect from frost.
HSE CONDITIONS	Please follow safety instructions from the Safety Data Sheet and comply with workplace safety laws. The general rule is to avoid contact of the product with the skin and eyes. Notice ! Always follow all precautionary, health and safety notice from the Safety Data Sheet and container labels.
DISCLAIMER	All data in this document have been prepared for informational purpose only. We cannot take responsibility for the results of user actions over which we have no control. The user is responsible for making the control sample and determining the suitability of the product for specific, individual applications. Company Troton Sp. z o.o. does not take responsibility for any damage, or loss of profits associated with the improper use of the products. All information is based on scrupulous laboratory research and many years of experience. Our position of market leadership does not free us from constant quality control of our products. However, we do not accept responsibility for the effects of improper use or storage of our products, or the effects of using our products in any way contrary to the standard of good workmanship.
QUALITY QUARANTEE	Production, quality control and the realization of deliveries fulfill the demands of ISO 9001 and 14001 standards.